















GENERATING SET GE 7000 HSX



FEATURES

- Engine shut down for low oil level
- Electric starter
- Sockets: 1x230V 32A 2P+T CEE - 1x230V 16A 2P+T CEE
- ELCB-GFI (Ground Fault Interruptor)
- Circuit breaker
- Super Silenced
- Ready for connection to automatic transfer unit EAS
- Meets EC Directives for safety and noise level

The images are for reference

Standard Equipment 										
	GS Synchronous alternator		D ELCB-GFI	MT Circuit breaker		T Thermal shut off				
 Options on request	<ul style="list-style-type: none"> • Earthing kit • Automatic transfer unit (AMF) EAS 15-806 		<ul style="list-style-type: none"> • Remote control TCM15 • Exhaust extension 			<ul style="list-style-type: none"> • Moving wheels CTM7 				
 Versions on request	<ul style="list-style-type: none"> • Schuko sockets 									

Technical data

GE 7000 HSX

A.C. GENERATION - 50 Hz - *Single-Phase synchronous alternator, self-excited, self-regulated, brushless*

*Stand-by single-phase power	6.7 kVA (6 kW) / 230 V / 29.1A
*PRP single-phase power	5.5 kVA (5 kW) / 230 V / 23.9A
Cos φ	0.9
Insulation class	H

* Output powers according to ISO 8528-1

ENGINE - 4-stroke petrol, OHV, Air cooling

Model	Honda GX 390
* Stand-By net power	8.2 kW (11.1 HP)
* PRP net power	6.4 kW (8.7 HP)
Cylinders/ Displacement	1/ 389 cm ³
Speed	3000 rpm
Fuel consumption (75% of PRP)	2.4 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity	20 l
Running time (75% of PRP)	8.3 h
IP protection degree	IP 23
* Dimensions LxIxh	1060x570x665 mm
* Dry weight	155 kg
** Measured acoustic power LwA (pressure LpA)	88 dB(A) (63 dB(A) @ 7m)
** Guaranteed acoustic power LwA (pressure LpA)	89 dB(A) (64 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer / **Acoustic power according to European Directive 2000/14/EC

Mosa reserves the right to change this specification without notice. For further information please contact the sales department.