

.ZIP

Power range 6,5-13 kVA

Generating sets 3000 /3600 rpm 50/60Hz - 400-230 V/480-240V
3000 rpm Diesel / Gasoline/ Methane Gas / LPG Gas



Super Silent 65/67 dBA
Super silenziosi 65/67DbA



Tank on board
Serbatoio a bordo



For Domestic use
Per uso domestico

**Generating sets designed to offer
silent portable power solutions**

**The ZIP series generators offer
a wide range of uses**

**Gruppi elettrogeni studiati per
offrire soluzioni energetiche
portatili e silenziose**

**La serie di gruppi elettrogeni ZIP offre un'ampia
gamma di utilizzi**

HITG[®]
HIGH-TECH GENERATORS

Authorised Australian Distributor



GE.ZIP

Power Generators Super silent

3000 RPM DIESEL / GASOLINE / METHANE
GAS / LPG GAS
50 / 60 HZ 400/480 V



KVA KW



KVA KW



BRAND



COOLING



CODE



SPEED GOVERNOR



CYLINDERS



TANK LTS



RUNTIME h



NOISE dbA



DIMENSIONS cm



WEIGHT Kg

Gasoline - Benzina Electric start up - Avviamento elettrico With AVR - Con AVR

Model	6,5	5,2	-	-	Brand	Cooling	Code	Speed Governor	Cylinders	Tank LTS	Runtime h	Noise dbA	Dimensions cm	Weight Kg
GE.ZIP-075-S-BM-AE	6,5	5,2	-	-	Subaru	Air	EX40	M	1L	19	9	65	103 x 62 x 80	193
GE.ZIP-075-S-BT-AE	3,0	2,4	8,1	6,48	Subaru	Air	EX40	M	1L	19	9	65	103 x 62 x 80	212
GE.ZIP-120-K-BM-AE	12,0	9,6	-	-	Kohler	Air	CH730	M	2V	49	8	64	110 x 54 x 93	247
GE.ZIP-120-K-BT-AE	6,0	4,8	12,5	10	Kohler	Air	CH730	M	2V	49	8	64	110 x 54 x 93	255

Diesel - Diesel Electric start up - Avviamento elettrico With AVR - Con AVR

Model	6,5	5,2	-	-	Brand	Cooling	Code	Speed Governor	Cylinders	Tank LTS	Runtime h	Noise dbA	Dimensions cm	Weight Kg
GE.ZIP-065-Y-DM-AE	6,5	5,2	-	-	Yanmar	Air	L100	M	1L	19	15	69	103 x 62 x 80	222
GE.ZIP-065-Y-DT-AE	3,0	2,4	6,5	5,2	Yanmar	Air	L100	M	1L	19	15	69	103 x 62 x 80	224
GE.ZIP-120-K-DM-AE	12,0	9,6	-	-	Kohler	Air	KD425/2	M	2V	19	8	71	110 x 54 x 93	247
GE.ZIP-120-K-DT-AE	6,0	4,8	12,3	9,84	Kohler	Air	KD425/2	M	2V	19	8	71	110 x 54 x 93	250

Methane gas - Gas Metano Electric start up - Avviamento elettrico With AVR - Con AVR

Model	6,0	4,8	-	-	Brand	Cooling	Code	Speed Governor	Cylinders	Tank LTS	Runtime h	Noise dbA	Dimensions cm	Weight Kg
GE.ZIP-060-S-MM-AE	6,0	4,8	-	-	Subaru	Air	EX40	M	1L	-	1,1m3/h	65	103 x 62 x 80	210
GE.ZIP-070-S-MT-AE	3,0	2,4	6,0	4,8	Subaru	Air	EX40	M	1L	-	1,1m3/h	65	103 x 62 x 80	212
GE.ZIP-100-K-MM-AE	11,0	8,8	-	-	Kohler	Air	CH730	M	2V	-	3,3m3/h	64	110 x 54 x 93	247
GE.ZIP-120-K-MT-AE	5,0	4,0	11,0	8,8	Kohler	Air	CH730	M	2V	-	3,3m3/h	64	110 x 54 x 93	255

LPG Gas - Gas GPL Electric start up - Avviamento elettrico With AVR - Con AVR

Model	6,5	5,2	-	-	Brand	Cooling	Code	Speed Governor	Cylinders	Tank LTS	Runtime h	Noise dbA	Dimensions cm	Weight Kg
GE.ZIP-060-S-GM-AE	6,5	5,2	-	-	Subaru	Air	EX40	M	1L	-	1,1m3/h	65	103 x 62 x 80	210
GE.ZIP-070-S-GT-AE	3,0	2,4	6,5	5,2	Subaru	Air	EX40	M	1L	-	1,1m3/h	65	103 x 62 x 80	212
GE.ZIP-100-K-GM-AE	12,0	9,6	-	-	Kohler	Air	CH730	M	2V	-	3,3m3/h	64	110 x 54 x 93	247
GE.ZIP-120-K-GT-AE	5,0	4,0	12,0	9,6	Kohler	Air	CH730	M	2V	-	3,3m3/h	64	110 x 54 x 93	255

* Not to be taken simultaneously with the three-phase power - Non prelevabile contemporaneamente alla potenza trifase

Optional

Trailer kit



O.G-KT-05/06

Flex pipe



O.G-KS-30/35

Automatic Transfer Switch



QA.MPE.017B

Equipment - Dotazioni



SELF SUPPORTING FRAME
TELAIO AUTOPORTANTE



LIFTING HOOK
GANCIO DI SOLLEVAMENTO



TANK REFILLING POINT
BOCCHETTONE SERBATOIO



Locks
CHIUSURE



EXHAUST
SCARICO



BATTERIES
BATTERIE

Super Silent 65/67 dBA . SUPERSILENZIATI 65/67 DBA

Easy to service . ISPEZIONABILITÀ FACILITATA

Soundproofing internal insulation . ISOLAMENTO INTERNO FONOASSORBENTE

Start/stop emergency button externally accessible . FUNGO D'EMERGENZA ESTERNO

Residential muffler . MARMITTA RESIDENZIALE

Magneto-thermal breaker . INTERRUTTORE MAGNETOTERMICO

Tank on board . SERBATOIO INTEGRATO

Anti-overturning base frame . TELAIIO ANTIRIBALTAMENTO

Fuel gauge . INDICATORE LIVELLO CARBURANTE

Engine liquids included . LIQUIDI MOTORE INCLUSI

On board Control panels *Quadri a bordo*



Single-phase arrangement

Allestimento Monofase:

- N. 1 CEE 2P+T 32A 230V**
- N. 1 CEE 2P+T 63A 230V**
- N.1 Shuko 16A 230V**

Three-phase arrangement

Allestimento Trifase:

- N. 1 CEE 2P+T 32A 230V**
- N. 1 CEE 3P+N+T 32A 400V**
- N. 1 Shuko 16A 230V**

Equipment - dotazioni

- Voltmeter** - Voltmetro
- Frequency-meter** - Frequenzimetro
- Starting key** - Blocco chiave
- Battery fuse** - Fusibile per batteria
- Connector for ATS panel** - Connettore quadro automatico
- Emergency stop button** - Pulsante emergenza
- Circuit breaker** - Interruttore magnetotermico
- Thermal circuit breaker** - Disgiuntore termico
- Grounding** - Collegamento a terra



HITG®

HIGH-TECH GENERATORS



ELCOS
POWER GENERATORS

ELCOS SRL
Strada Statale 234 Km 58.250 -
26023 Grumello Cremonese CR - Italy
tel +39 0372 72330 - fax +39 0372 7233220
PI 01084730199
info@elcos.net - elcos@pec.elcos.net



POWER GENERATORS
14 0372 3... and a one pack...

Ph: 1300 743 529

E: sales@hightechgenerators.com.au

www.hightechgenerators.com.au



www.elcos.net